

STANDARD EQUIPMENTS

- BILATERAL TILTING TANK BY DOUBLE EFFECT RAM AND QUICK CONNECTION WITH TRACTOR OIL
- STAINLESS STEEL AISI 304 FLOWER
 EMBOSSING TANK FOR FOOD CONVEYING
 WITH BRUSHED STAINLESS STEEL AND TIG
 WELDED SHELL
- FLOW DIVIDER HYDRAULIC ENGINE
- FRUITS FLOW CONTROL PANEL
- THE LOWER CENTRE OF GRAVITY ALLOWS
 THE VEHICLE BOTH TO STAY FIRMLY ON THE
 ROAD AND DURING UNLOADING
- FOOT STAND SET UP
- HIGH RESISTANCE REINFORCED STRUCTURE
- LEAF SPRING SUSPENSIONS WITH "ADR" 8
 COLUMNS INCREASED AXLES (DRL 140-200)
- HYDRAULIC OR AIR BRAKE WITH AUTOMATIC SHUT OFF PARKING BRAKE
- BRAKE CORRECTING DEVICE (ONLY FOR AIR BRAKING SYSTEM)

- INDUSTRIAL TWHEEL WITH 8 HOLES INDUSTRIAL RIM
- POLYURETHANE PAINT WITH EPOXORY PRIMER, HIGH WEAR RESISTANCE
- PARACHUTE END-STROKE VALVE
- HYDRAULIC FOOT STAND (SOLO PER DRL 100-120-140-200)
- QUICK CONNECTIONS SUPPORT AND 7-POLE SOCKET
- REAR ZINC-COATED METAL SHEET BUMPERS AND RUBBER BUMPERS
- REMOVABLE ZINC-COATED IRON FENDERS WITH RUBBER BUMPERS AND REAR SPLASH-PROOF
- LIGHTING SYSTEM WITH INDUSTRIAL LIGHTS
- VEHICLES REGISTRATION CERTIFICATES

TECHNICAL INFORMATION



MOD.	DRL 100	DRL 120 N	DRL 140 N
Dimensions (cm)	220x400 - H sideboard: 100	240x400 - H sideboard: 150	240x470 - H sideboard: 150
Axles No.	2	2	2
Total capacity rate (kg)	10000	12000	14000
Unladen Weight (kg)	2380	2750	3600
Tank capacity (m³)	8,5	10,5	12,5
Pneumatic	435/50 R19.5	435/50 R19.5	435/50 R19.5
Braking	PNEUMATICS HYDRAULIC	PNEUMATICS HYDRAULIC	PNEUMATICS HYDRAULIC



OPTIONAL



ZINC-COATED TOOLBOX



STAINLESS STEEL TOOLBOX



SIDE STABILIZER STAND FOOT



STEERING AXLE



STAINLESS INSPECTION STEPLADDER



TARPAULIN HOSE AND HOOK



WATER JERRY CAN



REAR FENDER WITH STAINLESS STEEL LIGHTS



SEMIAUTOMATIC COVERAGE WITH TARPAULIN