

# DRF AUGER

FARMING TRAILER WITH AUGER EMPTYING SYSTEM.  
SCISSOR LIFT SYSTEM AVAILABLE. UP TO 6.000 KG CAPACITY.



## STANDARD EQUIPMENTS

- PANTOGRAPH SHELL WITH TEFLON BUSHING AND HYDRAULIC LIFTING
- STAINLESS STEEL AISI 304 20/10 FLOWER EMBOSSED TANK FOR FOOD CONVEYING WITH BRUSHED STAINLESS STEEL AND TIG WELDED SHELL
- HYDRAULIC GEARED MOTOR WITH STAINLESS STEEL COUPLING BUSHINGS
- EMPTYING BY STAINLESS STEEL AUGER AISI 304 WITH TEFLON BLADE
- MANUAL OPENING REAR DOOR WITH HERMETICALLY SEALED GASKET
- ADJUSTABLE EMPTYING SPEED
- PIVOTS AND BUSHING WITH GREASER NIPPLES
- REAR ZINC-COATED METAL SHEET BUMPERS AND RUBBER BUMPERS
- REMOVABLE FENDERS WITH RUBBER BUMPERS
- SIDE HOOKS
- MECHANICAL PARKING BRAKE AND PREDISPOSITION FOR HYDRAULIC BRAKE (DRF 60C HYDRAULIC)
- POLYURETHANE PAINT WITH EPOXY PRIMER. HIGH WEAR RESISTANCE
- FOOT STAND
- QUICK CONNECTIONS SUPPORT AND 7-POLE SOCKET
- LIGHTING SYSTEM
- VEHICLES REGISTRATION CERTIFICATES



## TECHNICAL INFORMATION

MOD.	DRF 25C	DRF 30C	DRF 50C	DRF 60C
Dimensions (cm)	140x270	160x300	180x300	180x400
Total capacity rate (kg)	2500	3000	6000	6000
Unladen Weight (kg)	790	1000	1560	2230
Tank capacity (m <sup>3</sup> )	2	3	4,8	6,4
Auger diameter (cm)	30	30	40	40
Pneumatic	10,0/80 - 12 PR8	10,0/75 - 15,3 PR12	11,5/80 - 15,3 PR18	435/50 R19,5
Ground clearance (cm)	125 - 135	125 - 135	185 - 200	200 - 215
Emptying height (cm)	60 - 220	60 - 300	70 - 260	80 - 300

## OPTIONAL



HYDRAULIC BRAKE



INDEPENDENT HYDRAULIC DUMPING SYSTEM



ZINC-COATED TOOLBOX



STAINLESS STEEL TOOLBOX



SEMI-AUTOMATIC COVERAGE WITH TARPULIN



FIXED FLOW CONTROLLER



WEIGHT SYSTEM WITH PRINTER



HYDRAULIC STAND FOOT



WATER JERRY CAN



REAR HYDRAULIC DOOR



REAR FENDER WITH STAINLESS STEEL LIGHTS



2" BALL VALVE FLANGE/GAROLLA



REAR HYDRAULIC CONTROLS



DRIP GATE VALVE